

2D WIRED BARCODE SCANNER HC-5208S



- 1MP image frame rate up to 60fps
- Support OCR (Passport, ID card,driving license card,Visa Card etc.)
- Support USB, RS-232 and Virtual serial port.
- Can read all 1D/2D/Dotcode barcode on the screen and paper
- Can work with Win XP/7/8/10,iOS,Android system
- Strong decode ability to read difficult barcodes (blurred, wrinkled, fuzzy, low contrast,high density)

APPLICATION

Chain store, Retail , Supermarket,Health care , Clothing, Tobacco, etc.



1M pixel



1D



2D



Quick reading



Plug and play



Two color indicator



Automatic



Anti seismic anti falling

HC5280S TECHNICAL SPECIFICATION

OS Windows iOS / Android	Image Sensor CMOS	Image(Pixels) 1280 (H)*800 (v)pixels	light source Aiming: 625 nm LED; illumination:4000K LED	Scan Mode Handhand (Manual) / Handfree (Automatic)
FPS Frame Rate 60fps/s	Scan accuracy ≥ 4mil@ Code39	Print Contrast ≥ 20%	Visual Indicator Red and Blue LED Light , Buzzer	Interfaces USB keyboard, USB virtual serial port, RS-232
Scan Angle Left and right: ± 55 ° Front and rear: ± 55 ° Rotate: 360 °	Field of view 41° horizontal, 28° vertical	Transmission Mode Wired Transmission	Dimension H x W x L Scanner: 174*66*94 (mm)	Weight 205g (with cable)
Cable Standard 1.8M straight	Case Material ABS+PC, TPU	Power parameter Input Voltage: 5VDC±5% Working current: 190mA (Typical value) Standby current: 70mA	Environmental parameters Operating Temperature: -20°C~+40°C Working Humidity: 5% to 95% relative humidity, non-condensing Storage Temperature: -40°C~+70°C Electrostatic protection: ±8 kV (Direct discharge) Ambient brightness: 0~100,000Lux Drop Resistance : 2M IP: IP52	
Firmware Update Computer online upgrade	Safety regulations CE (EN 55032:2015; EN 55035:2017), ROHS, BIS, EN62368-1:2014+A11:2017 FCC PART 15 CLASS B	Scan distance 25-300mm @ EAN 13mil PCS=100%; 30-350mm @ QR 20mil PCS=100%		
Decoding Capability 1D: UPC/EAN/JAN,UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,Code 93, Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code,Code 32 (Italian Pharmacode), R5S-14, R5S-Limited, R5S-Expand, etc. 2D: QR Code, Data Matrix, PDF417, Aztec, Maxicode, Dotcode, GS1 DataBar stack, etc. OCR(Chinese ID card and some overseas national certificates)				

Optional configuration

- Scanner bracket**
Realize handfree scan